



# DiskStation DS216se

Synology DiskStation DS216se is a budget-friendly two-bay NAS device with the capability to host, share and protect data. Sharing the variety of packages in DSM Package Center, DS216se helps beginners explore the infinite possibilities of Synology NAS. Synology DS216se is backed with Synology's 2-year limited warranty.

# Highlights

- Floating point unit enabled for multimedia processing
- Affordable 2-Bay personal cloud for file sharing & backup
- Consumes only 5.12W in hibernation
- Scheduled power on/off further reduces energy consumption
- DLNA®-Certified media server
- Running on Synology DiskStation Manager (DSM)

# **Choice NAS for Everyone**

Centering on the core features of NAS devices, Synology DS216se provides handy and effective network storage under budget. Not only does DS216se centralize and back up your digital contents, it makes **cross-platform** and **cross-device sharing** effortless.

DS216se delivers an average **102 MB/s reading** speed under RAID 1 configuration in a Windows® environment, and over **59 MB/s writing**.¹ The built-in floating-point unit enhances the overall capability of the main CPU, and is particularly advantageous in speeding up thumbnail processing, making photo viewing a refreshingly new experience.

Equipped with Synology's full multimedia applications, DS216se is also an ideal solution for users looking for entertainment and download center, providing easy and energy-efficient download service as well as multimedia streaming capabilities. With Synology's rich cloud applications, DS216se serves as your personal cloud whose content is available anywhere on demand.

# **Easy Setup and Management**

**Web Assistant** is a web-based utility to make every DiskStation as easy to install as possible. Installation is done inside your existing web browser by setting up all vital system components in few simple steps. Combined with a quick start widget, users can simultaneously tour the DSM operating system and set it up to use right away.

For users unfamiliar with complicated router configurations or those who simply want to save time, **Synology EZ-Internet Wizard** simplifies the process of setting up access to DS216se from the Internet by walking through all of network settings including firewall, portforwarding, PPPoE setup and DDNS registration. **Synology Hybrid RAID** allows you to reach maximum use of your hard drive while keeping your storage safe with data redundancy.

### **Certified DLNA Media Server**

As a fully certified DLNA DMS (Digital Media Server), DS216se serves also as a ready media server with the capability to host digital multimedia contents for remote playback. Once connected to a wireless router, DS216se is set to stream music, photos and videos to DLNA-compliant devices without any pre-configuration, thus enabling users to enjoy their collection on larger screens or with quality speakers. Synology even makes it possible for users to browse and select DiskStation contents using **DS audio** - a handy mobile app - to designate a DLNA player within the same local network to play it.



### **Anytime Availability**

Access your DiskStation anywhere using Synology mobile apps.



### **Cross-platform File Synchronization**

Auto-synchronize your files among DiskStation, PC and mobile devices using Synology Cloud Station.

### **Anywhere/Anytime Availability**

**QuickConnect** and **EZ-Internet** configure your DS216se for accessing over the Internet with minimal effort. **Cloud Station** allows users to sync files among multiple devices, including Windows PC, Mac®, Linux®, iOS and Android tablets or phones, effortlessly keeping everything up-to-date. Combined with Synology's mobile apps for every popular feature, including **DS photo**, **DS audio**, and **DS video** for anywhere multimedia access, **DS download**, **DS file**, and **DS cloud** for seamless file download/access/synchronization, you can enjoy your NAS anywhere, any time.

## 24/7 Security Solution

Synology **Surveillance Station** offers a centralized interface to manage IP cameras deployed in your home, allowing users traveling miles away to safeguard the environment by watching live views, recording events, and taking snapshots with a computer or mobile device. DS216se is an ideal entry-level surveillance solution as it is capable of hosting up to **5 IP cameras** (50 FPS at 720p). In addition to its intuitive setup and hassle-free interface, Surveillance Station features an optimized live view experience with on-screen operations, smart analytics tools like motion detection, and an alert system that sends instant notification through **DS cam**, SMS, and e-mail.

# Running on Synology DiskStation Manager (DSM)

Synology DiskStation Manager (DSM) is a web-based OS that provides private cloud service. It is designed to make your everyday living easier. The **multi-tasking web UI** allows you to run multiple applications simultaneously on one browser tab and switch between them instantly. The simple interface allows you to obtain and configure storage capacity with minimal friction. It provides you with complete control of your personal cloud and lets you access it anywhere.

The built-in **Package Center** allows you to download and install the packages designed specifically for your unique needs, whether it's sharing files on the cloud, sharing photos on an online album, or setting up a VPN environment. All will happen with just a few clicks.


## **Energy Efficient Design**

Synology DS216se is designed with energy efficiency in mind. Compared with its average PC counterpart, Synology DS216se consumes relatively little power at 13.73 watts while accessing and 5.12 watts when hard drive hibernation is enabled. The scheduled power on/off feature further reduces power consumption and operation cost.

All Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology acknowledges the responsibility as a global citizen to continually work to reduce the environmental impact of every product produced.

# **Connections & Buttons**





| 1 LED in | ndicator 2 | Power button | 3 | Fan                      | 4 | USB 2.0 port |
|----------|------------|--------------|---|--------------------------|---|--------------|
| 5 Reset  | button 6   | LAN port     | 7 | Kensington Security Slot | 8 | Power port   |

# **Technical Specifications**

# Hardware

| CPU                           | Marvell Armada 370 800MHz  |
|-------------------------------|--|
| Floating point unit           | Yes  |
| Hardware encryption engine    | Yes  |
| RAM size                      | DDR3 256MB   |
| Compatible drive type         | 3.5"/2.5" SATA III/II x 2 (Hard drives not included. Disk holders are required for 2.5" drives.) |
| Maximum internal raw capacity | 16TB (8TB HDD x 2) (The actual capacity will differ according to volume types.)                  |
| External ports                | USB 2.0 port x 2   |
| Size (HxWxD)                  | 165 mm x 100 mm x 225.5 mm   |
| Weight                        | 870g   |
| LAN                           | Gigabit (RJ-45) x 1  |
| Wireless support              | Yes (wireless dongles not included)  |
| Scheduled Power on/off        | Yes  |
| AC input power voltage        | 100V to 240V AC  |
| Power frequency               | 50Hz to 60Hz, single phase   |
| Operating temperature         | 5°C to 40°C (40°F to 104°F)  |
| Storage temperature           | -20°C to 60°C (-5°F to 140°F)  |
| Relative humidity             | 5% to 95% RH   |
|                               |  |

# General

| Networking protocols    | CIFS, AFP, NFS, FTP, WebDAV, CalDAV, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN™, L2TP)   |
|-------------------------|--|
| File system             | Internal: ext4 External: ext4, ext3, FAT, NTFS, HFS+ (read only)   |
| Storage management      | Maximum single volume size: 16TB, Maximum internal volume: 256   |
| Supported RAID type     | Synology Hybrid RAID (SHR), Basic, JBOD, RAID 0, RAID 1  |
| File sharing capability | Maximum user account: 512, Maximum group: 128, Maximum shared folder: 256, Maximum concurrent CIFS/AFP/FTP/File Station connection: 64   |
| Privilege               | Windows Access Control List (ACL)  |
| Directory service       | Windows AD Integration: Domain Users login via Samba (CIFS)/AFP/FTP/File Station, LDAP integration   |
| Security                | FTP over SSL/TLS, IP auto-block, firewall, encrypted network backup over Rsync, HTTPS connection   |
| Utilities               | Synology Web Assistant, Synology Assistant, Cloud Station, Photo Station Uploader  |
| Supported clients       | Windows XP onwards, Mac OS X® 10.7 onwards, Ubuntu 12 onwards  |
| Supported browsers      | Chrome™, Firefox®, Internet Explorer® 8 onwards, Safari® 7 onwards, Safari (iOS® 7 onwards on iPad®), Chrome (Android 4.0 onwards on tablets)  |
| Language                | English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar,<br>Português do Brasil, Português Europeu, Türkçe, Český, 日本語, 한국어, 繁體中文, 简体中文 |

# **Applications**

| File Station                | Virtual drive, remote folder, Windows ACL editor, compress/extract archived files, bandwidth control for specific users or groups, create sharing links, transfer logs              |
|-----------------------------|---|
| Backup solutions            | Network backup; local backup; desktop backup; configuration backup; OS X Time Machine; backup data to public cloud; shared folder sync - maximum task number: 2                     |
| Mail Server                 | Supported Mail Server protocols: POP3, SMTP, IMAP, support LDAP/AD account  |
| FTP Server                  | Bandwidth control for TCP connections, custom FTP passive port range, anonymous FTP, FTP SSL/TLS and SFTP protocols, boot over the network with TFTP and PXE support, transfer logs |
| Web Station                 | Virtual host (up to 30 websites), PHP/MariaDB®, 3rd-party applications support  |
| Printer Server              | Maximum printer: 2, printing protocols: LPR, CIFS, IPP, iOS printing, Google Cloud Print™, multi functional print server (MFP functions are for Windows PC only)                    |
| Storage Analyzer            | Volume and quota usage, total size of files, volume usage and trends based on past usage, size of shared folders, largest/most/least frequently modified files                      |
| Security Advisor            | Malware detection/removal, user account/password, network, system-related security scan   |
| Log Center                  | SSL connection, log rotation: 6 months, 1 year, 2 years, 3 years, email notification  |
| iOS/Android™ applications   | DS cloud, DS file, DS finder, DS cam, DS note, DS audio, DS download, DS photo, DS video  |
| Windows Phone® applications | DS file, DS finder, DS audio, DS download, DS photo, DS video   |
|                             |   |

# **Add-on Packages**

| Surveillance Station    | Maximum IP camera #: 5 (total of 50 FPS at 720p, H.264) (Including two free camera licenses. Procurement of additional licenses is required.)   |
|-------------------------|---|
| VPN Server              | Maximum connections: 5; supported VPN protocols: PPTP, OpenVPN™, L2TP   |
| Mail Station            | Webmail interface for Mail Server; receiving mails from multiple POP3 mailboxes, customizable SMTP server   |
| Cloud Station           | Maximum concurrent file transfers: 64, retain historical and deleted file versions  |
| Cloud Sync              | One or two-way synchronization with public cloud storage providers including Amazon Cloud Drive, Amazon S3-compatible storage, Baiduyun, Box, Dropbox, Google Cloud Storage, Google Drive, hubiC, Megafon Disk, Microsoft OneDrive, OpenStack Swift-compatible storage, WebDAV servers, Yandex Disk |
| DLNA/UPnP® Media Server | DLNA certified, PS3*/PS4*/Xbox 360*/Xbox One* support   |
| Note Station            | Rich-text note organization with versioning, encryption, sharing, media embedding and attachments   |
| Download Station        | Supported download protocols: BT/HTTP/FTP/NZB/eMule Maximum concurrent download task: 20  |
| Other packages          | Photo Station, Audio Station, iTunes® Server, 3rd-party packages  |
|                         |   |

# **Environment and Packaging**

| Environment          | RoHS Compliant   |
|----------------------|--|
| Package content      | DS216se main unit, Welcome note, accessory pack, AC power adapter, RJ-45 LAN cable |
| Optional accessories | Camera License Pack, VS360HD, Disk Holder (Type C)                                 |
| Warranty             | 2 Years  |

 $<sup>{}^*\!</sup>Model\,specifications\,are\,subject\,to\,change\,without\,notice.\,Please\,refer\,to\,www.synology.com\,for\,the\,latest\,information.$ 

### SYNOLOGY INC.

Synology is dedicated to taking full advantage of the latest technologies to bring businesses and home users reliable and affordable ways to centralize data storage, simplify data backup, share and sync files across different platforms, and access data on-the-go. Synology aims to deliver products with forward-thinking features and the best in class customer services.

Copyright © 2015, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan.

DS216se-2015-ENU-REV001

### Headquarters

Synology Inc. 3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

### Chino

Synology Shanghai 20070, Room 516, No. 638, Hengfeng Rd., Zhabei Dist., Shanghai, China

### France

Synology France SARL 39 rue Louis Blanc, 92400 Courbevoie, France Tel: +33 147 176288

### North & South America

Synology America Corp. 3535 Factoria Blvd SE #200, Bellevue, WA 98006, USA Tel: +1 425 818 1587

### **United Kingdom**

Synology UK Ltd. Unit C, Denbigh West Business Park, Third Avenue, Bletchley, Milton Keynes, MK1 1DH, UK Tel: +44 1908 366380

### Germany

Synology GmbH Grafenberger Allee 125 40237 Düsseldorf Deutschland Tel: +49 211 9666 9666

<sup>1.</sup> Performance figures could vary on different environments.