Synology®



DiskStation DS2415+

Synology DiskStation DS2415+ features an all-new quad core CPU with an AES-NI hardware encryption engine, providing outstanding performance and data encryption acceleration. With four built-in Gigabit LAN ports and scalability of up to 24 drives, Synology DS2415+ is the ideal storage solution for centralizing data backups, protecting critical assets and sharing files across different platforms. Synology DS2415+ is backed with Synology's 3-year limited warranty.

Highlights

- Quad Core CPU Delivers 451.5
 MB/s Reading, 415.49 MB/s
 Writing
- AES-NI Hardware Encryption
 Engine Boosts Encryption
 Transfer at over 451.21 MB/s

 Reading, 198.46 MB/s Writing
- Four Gigabit LAN Ports with Failover and Link Aggregation Support
- Scale up to 24 drives with Synology DX1215
- Expandable RAM Module (Up to 6GB)
- VMware®, Citrix®, Microsoft®
 Hyper-V® Certified
- High Availability and SSD
 Read/Write Cache Support
- Running on Synology
 DiskStation Manager (DSM)

Safeguards Your Big Data with Superior Performance

In the era of big data, finding a place to store and share tones of business files while maintaining data safety is extremely important for small and medium-sized businesses, and Synology DS2415+ is the ideal solution. With a brand-new quad core CPU, built-in AES-NI hardware encryption engine and expandable RAM module up to 6GB, DS2415+ delivers up to an average 451.5 MB/s reading and 415.49 MB/s writing speed under RAID 5 configuration in a Windows® environment,¹ and an encrypted data transmission at over 451.21 MB/s reading and 198.46 MB/s writing.

Virtualization Certified

DS2415+ provides seamless storage solutions for virtualization environments, including VMware®, Citrix®, and Hyper-V®. Being VMware vSphere 5® and VAAI® integration certified, DS2415+ helps offload specific storage operations and optimizes computation power for unparalleled performance and efficiency in VMware environments. As the centralized storage of a virtual environment, DS2415+ enables virtual machine migration, allowing movement from server to server whilst eliminating service downtime and disruption to user. Windows® Offloaded Data Transfer (ODX) and Synology Advanced LUN support extremely improves the efficiency on massive data transfer and migration.

Feature-Rich Business Applications

Put your data to work with Synology's DS2415+. With Windows® ACL and LDAP support, DS2415+ fits easily into any existing workgroup environment, providing detailed access control and efficient privilege settings. SMB applications including printer sharing, VPN Server, Mail Server, web server, anti-virus, and network video surveillance, allow a single Synology DS2415+ to replace several traditional computing devices and help to maximumimize your productivity while keeping cost and effort to a minimum.



Figure 1) Reliability, Availability & Disaster Recovery

Synology High Availability ensures seamless transition between clustered servers in the event of server failure with minimal impact to businesses.



Figure 2) Superior Performance

Multiple LAN ports with link aggregation support allows DS2415+ to deliver superior performance.

Resilient and Reliable

In addition to its superior performance, DS2415+ is built for reliability. **Four Gigabit LAN ports** provide redundancy in the event of unexpected hardware failure while hot swappable drives also help to minimize system downtime during drive replacement.

Uninterrupted availability is a critical goal for all businesses; however, many businesses worldwide still remain unprepared for disaster. **High Availability Manager** can ensure a seamless transition between clustered servers in the event of server failure with minimal impact to applications, thus decreasing the risk of unexpected interruptions and costly downtime.

Unparalleled Flexibility

As your data storage needs grow, Synology's DS2415+ can grow with you. DS2415+ can be connected to dedicated expansion units for additional storage on the fly, growing capacity with minimal effort. When paired with **Synology DX1215 expansion units**² through specially designed expansion cable, raw capacity can be as high as 144TB.

Easy Backup Solutions

To protect your critical business data, DS2415+ can become a centralized backup target for consolidating fragmented and unstructured information across your network through a range of options. Advanced backup privilege management makes network backup tasks safer and efficient. **Cloud Station** with selective sync and ACL control provides real-time data backup and synchronization among multiple computers and mobile devices. Complete backup solutions including **Scheduled LUN Snapshot**, **LUN clone** and **Backup & Replication** minimize the impact of disasters.

Energy Efficient and Easy Management Design

Synology DS2415+ is designed with energy efficiency in mind. Equipped with a **fast detachable fan module** with two 120 X 120mm fans and a smart airflow design, DS2415+ runs cool 24/7, while its noise dampening design makes it much quieter than PC counterparts. Hard drive hibernation further reduces power consumption and operation costs. **Screwless drive trays** make failed drive replacement fast and tool-free.

All Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology acknowledges the responsibility as a global citizen to continually work to reduce the environmental impact of every product produced.

Connections & Buttons



Technical Specifications

Hardware

| CPU | Intel Atom C2538 Quad Core 2.4GHz |
|-------------------------------|---|
| Hardware Encryption Engine | Yes (AES-NI) |
| Floating Point Unit | Yes |
| RAM Size | DDR3 2 GB (Expandable up to 6 GB) |
| Internal HDD/SSD | 3.5" or 2.5" SATA(II) X 12 (hard drives not included) |
| Maximum Internal Raw Capacity | 72 TB (6 TB HDD X 12) (The actual capacity will differ according to volume types) |
| Hot Swappable Drive | Yes |
| External Ports | USB 3.0 ports X 4, expansion port X 1 |
| Size (HxWxD) | 270 X 300 X 340 mm |
| Weight | 9.24 kg |
| LAN | Gigabit X 4 |
| Wake on LAN/WAN | Yes |
| Wireless Support | Yes (wireless dongles not included) |
| AC Input Power Voltage | 100V to 240V |
| Power Frequency | 50 Hz to 60 Hz, Single Phase |
| Operating Temperature | 5°C to 35°C (40°F to 95°F) |
| Storage Temperature | -20°C to 60°C (-5°F to 140°F) |
| Relative Humidity | 5% to 95% RH |
| | |

General

| General | |
|-------------------------|--|
| Networking Protocols | CIFS, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN™, L2TP) |
| File System | Internal: EXT4 External: EXT4, EXT3, FAT, NTFS, HFS+ |
| Storage Management | Maximum Single Volume Size: 108 TB, Maximum Internal Volume #: 512, Maximum iSCSI Target #: 32, Maximum iSCSI LUN#: 256; Raid Clone/Snapshot support; Supported RAID Type: Synology Hybrid RAID, Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 6, RAID 10; Synology Expansion Unit Support: DX513, DX213 |
| File Sharing Capability | Maximum User Account: 2048, Maximum Group: 256, Maximum Shared Folder: 512, Maximum Concurrent CIFS/AFP/FTP Connections: 512 |
| Privilege | Windows® Access Control List (ACL) |
| Directory Service | Windows® AD Integration: Domain Users login via Samba (CIFS)/AFP/FTP/File Station, LDAP Integration |
| Virtualization | VMware vSphere® 5, Microsoft Hyper-V®, Citrix® Certified |
| Security | FTP over SSL/TLS, IP Auto-Block, Firewall, Encrypted Network Backup over Rsync, HTTPS Connection |
| Utilities | Synology Assistant, Cloud Station, Evidence Integrity Authenticator |
| Supported Clients | Windows XP® onward, Mac OS X® 10.5 onward, Ubuntu® 9.04 onward |
| Supported Browsers | Chrome®, Firefox® Internet Explorer®: 8 or onward, Safari® 5 or onward, Safari (iOS 5 or later on iPad®), Chrome (Android™ 4.0 on tablets) |
| | |

| Language | English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Mag Português do Brasil, Português Europeu, Türkçe, Český, 日本語, 한국어, 繁體中文, 简体中文 |
|------------------------------|--|
| Applications | |
| File Station | Virtual Drive, Remote Folder |
| Backup Solutions | Network Backup, Local Backup, Desktop Backup, Shared Folder Sync - Maximum Task Number: 8, Configuration Backup |
| Mail Server | Supported Mail Server Protocols: POP3, SMTP, IMAP |
| FTP Server | Bandwidth Control, Custom FTP Passive Port Range, Anonymous FTP, Transfer Log |
| Web Station | Virtual Host (up to 30 websites), PHP/MySQL®, 3rd-Party Applications Support |
| Printer Server | Maximum Printer #: 2, Printing Protocols: LPR, CIFS, IPP, Apple iOS Printing, Google Cloud Print™, Multi Functional Print Server (MFP functions are for Windows PC only) |
| Log Center | SSL Connection, Log Rotation: 6 months, 1 year, 2 years, 3 years, Email Notification |
| iOS/Android™ Applications | DS audio, DS cam, DS cloud, DS download, DS file, DS finder, DS photo+, DS video, DS note |
| Windows Phone® Applications | DS audio, DS download, DS file, DS finder, DS photo+, DS video |
| Add-on Packages | |
| Surveillance Station | Default IP cam #: 2, Maximum IP cam # (licenses required): 40 (with two free licenses to install two IP cameras. Additional licenses can be purchased to expand the license quota.) |
| VPN Server | Maximumimum Connections : 20, VPN Method: PPTP, OpenVPN™ |
| Mail Station | Webmail Interface for Mail Server, Receiving Mails from Multiple POP3 Mailboxes, Customizable SMTP Server |
| Antivirus Essential | Full System Scan, Scheduled Scan, White List Customization, Virus Definition Auto Update |
| Cloud Station | Maximumimum Concurrent File Transfers: 512, Retain Historical and Deleted File Versions |
| Cloud Sync | Data Sync with Public Cloud Services: Dropbox, Google Drive, Baidu, Microsoft OneDrive, Box and hubiC |
| DLNA®/UPnP® Media Server | DLNA compliant, PS3®/Xbox 360® supported |
| Download Station | Supported Download Protocols: BT/HTTP/FTP/NZB/eMule Maximumimum Concurrent Download Tasks: 80 |
| Note Station | Rich-Text Note Organization with Versioning, Encryption, Sharing, Media Embedding and Attachment |
| Other Packages | Photo Station, Audio Station, iTunes® Server, 3rd-party packages |
| Environment and Packa | ging |
| Environment | RoHS Compliant |
| Package Content | DS2415+ Main Unit, Welcome Note, Accessory Pack, AC Power Cord, RJ-45 LAN Cable X 2 |
| Optional Accessories | Remote, Camera License Pack, Expansion Unit (DX1215), 4GB DDR3 RAM Module |

^{*}Model specifications are subject to change without notice. Please refer to www.synology.com for the latest information.

3 years

SYNOLOGY INC.

Warranty

Synology is dedicated to taking full advantage of the latest technologies to bring businesses and home users reliable and affordable ways to centralize data storage, simplify data backup, share and sync files across different platforms, and access data on-the-go. Synology aims to deliver products with forward-thinking features and the best in class customer services.

Copyright © 2014, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan.

DS2415+-2014-ENU-REV001

Headquarters

Synology Inc. 3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

China

Synology Shanghai 20070, Room 516, No. 638, Hengfeng Rd., Zhabei Dist., Shanghai

France

Synology France SARL 39 rue Louis Blanc, 92400 Courbevoie France Tel: +33 147 176288

North & South America

Synology America Corp. 13343 NE Bel-Red Road, Bellevue, WA 98005 USA

Tel: +1 425 818 1587

United Kingdom

Synology UK Ltd. Unit C, Denbigh West Business Park, Third Avenue, Bletchley, Milton Keynes, MKI 1 DH, UK Tel: +44 1908 366380

Germany

Synology GmbH Grafenberger Allee 125 40237 Düsseldorf Deutschland Tel: +49 211 9666 9666

^{1.} Performance figures could vary on different environments.

^{2.}DS2415+ supports one Synology DX1215, sold separately.